

# Hisense

# HS5500

## Self Ordering System

**Let Us Design One  
For You**



The Hisense HS5500 Self Ordering System provides an easy and contemporary approach to efficient service by speeding up the ordering process and reducing lines. Customers will enjoy the convenience, speed and simplicity of ordering by themselves while retailers benefit with improved labor efficiency, reduced customer queues, fewer walk-aways, increased transaction amounts and reduced order errors, all of which contribute to increased profits.

- 27" LCD Screen with Projected Capacitive Touch (PCT)
- Intel Bay Trail Celeron Quad Core J1900 2GHz High Speed CPU
- Tempered Glass Flat Front Panel
- Optional Facial Recognition Camera
- Electronic Payment Processing Terminal Bracket
- Integrated Thermal Receipt Printer
- Supports Wall Mount or Optional Stand

*Shown with the optional electronic payment processing terminal bracket. Use the payment processing terminal of your choice.*

## Standard Features

- 27" LCD Screen
- Projected Capacitive Touch (PCT)
- Intel Bay Trail Celeron Quad Core J1900 2GHz High Speed CPU
- Tempered Glass Flat Front Panel
- Integrated 3W Dual Speakers
- Integrated Thermal Receipt Printer
- Exceptional Cable Management

## Options and Upgrades

Configure your system with these easy to add options:

- Base and Stand Can Accomodate Two HS5500 Terminals
- 2D Honeywell Barcode Scanner
- Single Lens Camera
- Dual Lens Camera – Facial Recognition Capable
- Microphone
- WiFi Module
- 4G Module
- Electronic Payment Processing Terminal Bracket

## Connectivity

- A Two USB (V2.0)
- B COM1 – Powered
- C COM3 – Powered
- D LAN
- E Two USB (V2.0)
- F DC In (24V)
- G COM2 – Powered
- H One USB (V2.0) / One USB (V3.0)
- I USB (Speaker)
- J Two USB (V2.0)
- K Audio
- L VGA

## Specifications

<b>Processor:</b>	Intel Bay Trail Quad Core J1900 2GHz
<b>Cores / Threads</b>	Quad Core / 4 Threads
<b>Cache Memory:</b>	512KB L2
<b>Chipset (PCH):</b>	CPU Integrated
<b>Mass Storage Device:</b>	128GB 2.5" Solid State Drive
<b>RAM Memory (1 Slot):</b>	4GB SODIMM DDR3 (1333MHz) Expandable To 8GB
<b>Display LCD:</b>	Tempered True Flat 27" LCD with LED Backlighting
<b>Touch:</b>	Projected Capacitive Touch
<b>Resolution:</b>	1080P Resolution Ratio
<b>Brightness:</b>	300 cd/m <sup>2</sup> Adjustable
<b>Contrast Ratio:</b>	3000:1
<b>Response Time:</b>	< 12ms
<b>Backlight Life:</b>	> 30,000 Hours (Minimum)
<b>Color:</b>	>16.7M
<b>Integrated Speakers:</b>	Two Integrated 2.5 Watt Speakers
<b>Integrated Camera Option:</b>	Single Lens or Dual Lens
<b>Integrated Scanner Option:</b>	Honeywell 2D Scanner
<b>Depth of Field:</b>	0 ~ 6" (0 ~ 15mm)
<b>Resolution:</b>	5mil
<b>Printer – Size:</b>	80mm Thermal Printer with Cutter
<b>Speed:</b>	250mm per Second (10")
<b>Communication – Ethernet:</b>	RJ45 Gigabit Standard
<b>WiFi:</b>	Optional
<b>4G:</b>	Optional
<b>Current / Power Usage:</b>	0.55A / 60W 110V Environment
<b>Compatible O/S:</b>	POSReady 7 / Windows 7 Pro / Windows 10 Pro Windows 10 IoT Enterprise 2016 LTSP
<b>Dimensions – Overall:</b>	26-1/2"W x 71-1/4"H x 19"D
<b>Unit:</b>	19"W x 38-1/2"H x 4-1/2"D
<b>Base:</b>	26-1/2"W 66-1/2"H x 19"D
<b>Safety and EMI:</b>	FCC

